



## ENERG Y UA enepγua · ενεργεια IE IA



NIBE F1355-28

























 $\mathsf{A}^{\mathsf{+}}$ 

A

В

C

D

E

F

G







Supplier's name:	NI		
Model:	NIBE F	1355-28	
Temperature application	35	55	°C
Declared load profile for water			
heating		1	
Seasonal space heating energy	A++	A++	
efficiency class, average climate:			
Water heating energy efficiency			
class, average climate:			1
Rated heat output, average climate:	28 28		kW
Annual energy consumption for	11528	14621	kWh
space heating, average climate		11021	
Annual electricity consumption for			kWh
water heating, average climate		1	
Seasonal space heating energy	198	155	%
efficiency, average climate:			
Water heating energy efficiency,			%
average climate:	4-7		-ID
Sound power level LWA indoors	47		dB
Rated heat output, cold climate:	28	28	kW
Rated heat output, warm climate:	28	28	kW
Annual energy consumption for	12907	16450	kWh
space heating, cold climate			1
Annual electricity consumption for water heating, cold climate			kWh
Annual energy consumption for			+
space heating, warm climate	7237	9062	kWh
Annual electricity consumption for			
water heating, warm climate			kWh
Seasonal space heating energy	044	165	0/
efficiency, cold climate:	211	165	%
Water heating energy efficiency, cold			%
climate:			/0
Seasonal space heating energy	204	162	%
efficiency, warm climate:	201	102	/-
Water heating energy efficiency,			%
warm climate:			
Sound power level LWA outdoors		-	dB

## Data for package fiche

Controller class			
Controler contribution to efficiency	2		%
Seasonal space heating energy efficiency of package, average climate:	200	157	%
Seasonal space heating energy efficiency class for package, average climate:	A+++	A+++	%
Seasonal space heating energy efficiency of package, cold climate:	213	167	%
Seasonal space heating energy efficiency of package, warm climate:	206	164	%

Model(s):	NIBE F1355-28		
Type of heat source/sink:	Brine-to-water		
Low-temperature heat pump:	No		
Equipped with supplementary heater:	No		
Heat pump combination heater:	No		
Climate condition:	Average		
Temperature application:	Medium temperature (55 °C)		
Applied standards: EN14825, EN 14511 and EN12102			



Climate condition:				Average	,,, – – –		
Climate condition:			Madium	Average	ĺ		
Temperature application:	I FN140400		wieulum	temperature (55 °C)	ĺ		
Applied standards: EN14825, EN 14511 a	na EN12102 	2	1	Cananal anna haratar		1	1
		20.0	1111	Seasonal space heating		455	01
Rated heat output	Prated	28,0	kW	efficiency	$\eta_{s}$	155	%
Declared capacity for part load at outdoor tem	perature Tj			Declared coefficient of perfor	rmance for part load at outdo	oor temperatu	re Tj
Tj = -7 °C	Pdh	25,0	kW	Tj = -7 °C	COPd	3,1	kW
Tj = +2 °C	Pdh	15,3	kW	Tj = +2 °C	COPd	3,9	kW
Tj = +7 °C	Pdh	9,7	kW	Tj = +7 °C	COPd	4,6	kW
Tj = +12 °C	Pdh	4,3	kW	Tj = +12 °C	COPd	5,3	kW
Tj = biv	Pdh	28,0	kW	Tj = biv	COPd	2,8	kW
Tj = TOL	Pdh	28,0	kW	Tj = TOL	COPd	2,8	kW
Tj = -15 °C (if TOL < -20 °C)	Pdh		kW	Tj = -15 °C (if TOL < -20 °	C) COPd		kW
Bivalent temperature	T <sub>biv</sub>	-10	°C	Operation limit tempera	nture TOL	-10	°C
Cycling interval capacity for heating	Pcych		kW	Cycling interval efficiency			
Degradation co-efficient	Cdh	0,99	-	Heating water operating	·	65	°C
Power consumption in modes other than active	mode	,		Supplementary heater		I	
Off mode	P <sub>OFF</sub>	0,007	kW	Rated heat output	Psup	0,0	kW
Thermostat-off mode	P <sub>TO</sub>	0,035	kW				•
Standby mode	P <sub>SB</sub>	0,019	kW	Type of energy input		Electric	
Crankcase heater mode	P <sub>CK</sub>	0,025	kW				
Other items							
Capacity control		variable		Rated air flow rate, outo	doors		m³/h
. ,				Rated water flow rate, i	ndoor heat		
Sound power level, indoors/outdoors	$L_WA$	47/-	dB	exchanger			m³/h
				Rated brine or water flo	w rate,		
Annual energy consumption	$Q_{HE}$	14621	kWh	outdoor heat exchanger	•	3,40	m³/h
For heat pump combination heater:				Watanhaatiaa	ffict		0/
Declared load profile	<u> </u>			Water heating energy e	fficiency η <sub>wh</sub>		%
Daily electricity consumption	$Q_{\rm elec}$		kWh	Daily fuel consumption	Q <sub>fuel</sub>		kWh
Annual electricity consumption	AEC		kWh	Annual fuel consumptio			GJ
Approved by:							
Contact details	© NIRF Fr	nergy Systa	ems - Ro	x 14 - Hannabadsvägen 5 -	28521 Markarvd - Swe	den	
	I O TAIDE EI						